

L5 ANSWER 470 OF 575 CA COPYRIGHT 2004 ACS on STN
 AN 95:85243 CA
 ED Entered STN: 12 May 1984
 TI **Fly ash** fluxed flooring **composition**
 IN Kambor, Hans Ulrich; Wolter, Siegmund; Siebert, Peter; Winklhofer, Helmut;
 Liebmann, Georg
 PA Ger. Dem. Rep.
 SO Ger. (East), 5 pp.
 CODEN: GEXXA8
 DT Patent
 LA German
 IC E04F015-12; C04B031-10
 CC 58-5 (Cement and Concrete Products)
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	DD 143936	Z	19800917	DD 1979-213086	19790523
PRAI	DD 1979-213086		19790523		

AB An economical fluxed flooring compn. of easy workability and low
cement content is composed of **fly ash** 7-36,
cement 3-21, 0-4 mm sand 40-85, **water** 5-22, and concrete
 plasticizer 0.1-0.8 wt.%. The **product** is transported through
 pipes and easily applied on a floor. The strength of this flooring compn.
 is generally higher than that of anhydrite fluxed compns.

ST flooring compn **fly ash** sand

IT Sand

RL: USES (Uses)

(flooring compn., contg. **fly ash** and **cement**

)